



stts
Brazing solutions

STTS
Z.A.E. LA NEUVILLETTE
60240 FLEURY - FRANCE
☎ +33 3 44 49 02 19
✉ +33 3 44 49 11 40
✉ stts@stts-flux.com

**TECHNICAL
DATA SHEET**

FLUX IT 341B

. PRODUCT DESCRIPTION

Date of review :
29/09/2014
IR : 2

It is a flux paste intended for brazing Copper/Brass/Steel and Stainless Steel with all Silver alloys with a great pickling power. The flux residues are eliminated by thermal shock (dipping in cold water) or by brushing.

The paste Flux-it paste 341 B allows a very good adhesion even on a vertical surface. There is neither retention nor profusion, so it provides a good brazing stability while melting.

. CHARACTERISTICS - PHYSICO-CHEMICAL PROPERTIES, COMPOUND ELEMENTS

Homogeneous white paste without any boric acid

. PRODUCT APPLICATION

The Flux-it paste 341 B is advised for brazing by an oxy-acetylenic flame or by gas at temperatures between 550 and 750° C.

. DIRECTIONS FOR USE

The Flux-it paste 341 B is used by brushing or dipping the filler metal rod in the paste, then apply the filler metal rod coated on the pre-heated based metal.

. USING CARE AND RECOMMENDATIONS

No particular risk.
Refer to health and safety datasheet before use available on demand

