



stts
Brazing solutions

STTS
Z.A.E. LA NEUVILLETTE
60240 FLEURY - FRANCE
☎ +33 3 44 49 02 19
☎ +33 3 44 49 11 40
✉ stts@stts-flux.com

TECHNICAL DATA SHEET

FLUXIT 340 H

Date of review :
29/12/2014
IR : 2

. PRODUCT DESCRIPTION

It is a flux intended for brazing Copper/Brass/Steel and Stainless Steel with all Silver alloys with a great pickling powder. The waste of flux are eliminated by thermal shock (dipping in cold water) or by brushing.

At use, the powder Flux-it 340 H allows a very good adhesion even on a vertical surface. There are neither retention and nor profusion, so it allows a good stability in the brazing during melting.

. CHARACTERISTICS - PHYSICO-CHEMICAL PROPERTIES, COMPOUND ELEMENTS

Dry powder of calibrated granulometry without any boric acid

. PRODUCT APPLICATION

The powder Flux-it 340 H is advised for the brazing and the soudo-brazing by oxyacetylenic flame or by gas at temperatures between 550 and 880° C.

. DIRECTIONS FOR USE

The powder Flux-it 340 H is used in powder or it can be mixed with water in order to form a paste (80/20 flux/water) or it can be used by dipping the filler metal stick heated in the powder.

. USING CARE AND RECOMMENDATIONS

No particular risk.

Refer to health and safety datasheet before use available on demand

ISO 9001
ISO 14001
BUREAU VERITAS
Certification

